

GTS 19G HIGH-PERFORMANCE SUBWOOFER



Description

The GTS 19G is a single19" subwoofer module for the low-frequency extension in high-demanding touring and install applications, indoors and outdoors. Equipped with one high-excursion best-in-class transducer, it offers excellent reproduction quality and extreme sound pressure. The cabinet is provided with P-COM power connections on back panels

Features

- > 140 dB max SPL
- > 19" neo woofer, 4" v.c.
- > 2 side handles
- > Designed to operate with XPS 16K amplifier (8 modules per amp unit)
- > Durable and lightweight cabinet construction, polyurea coating
- > Heavy duty, powder coated, custom perforated front grille
- > 3 P-COM 8 pole bayonet connectors (Gold coated, CA-COM compatible, IP 68)

Part Number

13000862 GTS 19G

Black

EAN 8024530022082



GTS 19G

HIGH-PERFORMANCE SUBWOOFER

Acoustical specifications

Frequency Response (-10dB)

Max SPL @ 1m

Power section

Amplification

Nominal Impedance

Transducers

Woofer

Input/Output section

Input connectors
Output connectors

Standard compliance

Safety agency

Physical specifications

Cabinet/Case Material

Hardware Handles

Pole mount/Cap

Grille Color

Size / Weight

Height Width

Depth Weight 28 Hz ÷ 200 Hz

140 dB

Full Range

8 ohm

1 x 19" neo, 4.0" v.c

P-COM 8POLE P-COM 8POLE


CE compliant


Birch plywood M20 Socket 2 x side M20 thread Steel with clothing


Black

531.5 mm / 20.93 inches 760 mm / 29.92 inches 655 mm / 25.79 inches 48.5 kg / 106.92 lbs

Line Art 2D







531.5 mm / 20.95"

Technical Specifications Page 2 of 2