

# GTX 10 TWO-WAY LINE ARRAY MODULE



#### Description

The GTX 10 is a 2-way line array module for medium to large-scale, high-demanding touring and install applications, indoors and outdoors. Equipped with three best-in-class transducers, it offers excellent reproduction quality and optimized directivity. Up to 24 GTX 10 modules can be suspended on a single flybar.

#### Features

- > 143 dB max SPL
- > 4" titanium dome, neo compression driver
- > 2 x 10" neo woofers, 3" v.c.
- > 110° x 15° 4PATH waveguide
- > Designed to operate with XPS 16K amplifier (up to 6 modules per amp unit)
- > Durable and lightweight cabinet construction, polyurea coating
- > Heavy duty, powder coated, custom perforated front grille
- > 3 x P-COM 8 pole bayonet connectors (Gold coated, CA-COM compatible, IP 68)

**Part Number** 

13000796 GTX 10

Black

EAN 8024530021153



## **GTX 10**

### TWO-WAY LINE ARRAY MODULE

**Acoustical specifications** 

Frequency Response (-10dB)

Max SPL @ 1m

Horizontal coverage angle Vertical coverage angle

**Power section** 

Amplification

Nominal Impedance LF Nominal Impedance HF

**Transducers** 

Compression Driver

Woofer

Input/Output section

Input connectors
Output connectors

Standard compliance

Safety agency

**Physical specifications** 

Cabinet/Case Material

Hardware Handles Grille Color

Size / Weight

Height Width Depth

Weight

42 Hz ÷ 20000 Hz

143 dB 110° 15°

Bi-Amp 8 ohm 8 ohm

1 x 1.4" neo, 4.0" v.c 2 x 10" neo, 3.0" v.c

P-COM 8POLE
CE compliant
Birch plywood


P-COM 8POLE


Array fittings 1 x side, 2 rear Steel with clothing


Black


337 mm / 13.27 inches 750 mm / 29.53 inches 483.5 mm / 19.04 inches 31.5 kg / 69.45 lbs

Line Art 2D









Technical Specifications Page 2 of 2